

PIG® Grippy® Adhesive-Backed Absorbent Mat

MAT32100 Mediumweight, 32" x 100', 1 roll

Make the switch to the mat that sticks! Absorbent runner helps prevent slips, trips and falls around workstations and walkways near machinery in industrial facilities.

- Adhesive-backed absorbent mat stays exactly where you put it with no shifting, bunching up or flipping over to prevent slips, trips and falls in workstations and around machinery
- Proprietary adhesive sticks to the floor with a super-tight grip, but peels up easily for quick changeouts; reduces cleanup time to make your facility more productive
- Sticks to most commercial floor surfaces including concrete, VCT, linoleum, ceramic tile, quarry tile and laminate flooring
- Tough, spunbond top layer with heavy-duty zigzag stitching stands up to foot and light-wheeled traffic as well as heavy equipment driveovers; keep mat in service until it's saturated or shows signs of wear
- Eight layers of fine-fiber polypropylene safely absorb leaks, drips and overspray of oils, coolants, solvents and water
- Traps oil, grease and grime to keep them from being tracked around
- 32" x 100' roll provides enough length to create continuous coverage and absorbency in oily areas near machines and equipment
- Leakproof backing prevents absorbed liquid from soaking through to the floor
- Dark color hides grime so the mat looks cleaner longer
- Easy to cut and install: just roll it out, stick it down and smooth it out
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Absorbent Mat have been proven to reduce slip-and-fall claims by as much as 90%
- Mats take on the properties of absorbed liquids
 - always take proper precautions when handling saturated absorbents



Specifications

Antimicrobial	No
Traffic	Medium Foot Traffic
Backing Material	Adhesive-Backed
Indoor/Outdoor	Indoor Use
Incinerable	Yes
Flammability Specifications	Flame Resistant - Will melt and self-extinguish
Fluid Absorbed	Oils, Coolants, Solvents, Water – Universal
Color	Blue
Dimensions	32" W x 100' L
Mat Weight	Mediumweight
Recycled Content	25% or more Recycled Content
Absorbency	Up to 10.5 gal. per roll
Brand	PIG
Core Diameter	3"
Industry	Industrial Facilities; Shops & Garages
Perforated	No
Storage Temp Range	Store between 32°F and 120°F
Temperature Limit	Surface temps from 55°F to 120°F
Walking Surface	Absorbent Top
Sold as	1 roll
Weight	27 lbs.
New Pig Patent	Patent Pending
# per Pallet	13
Composition	Absorbent - Polypropylene Stitching - Polyester Adhesive Backing - Proprietary Adhesive Material
UNSPSC	47131901
UV Resistant	No
Pigalog® Page Number	Page 21

Metric Equivalent

Absorbency	Up to 39.7 L per roll
Dimensions	81.3cm W x 30m L
Weight	12.2 kg

Technical Information

Certifications, Approvals and Ratings

NFSI Certified,ANSI B101.1- 2009,Meets NFPA 99 Static Decay and Resistivity Requirements

Technical Documents

[PIG Grippy Mat](#)

[PIG® GRIPPY® ABSORBENT MAT PRODUCT DISCLAIMER & WARRANTY INFORMATION](#)

[Static Coefficient Of Friction \(SCOF\) Testing](#)

[How to use PIG Grippy Absorbent Mat](#)

[White paper – Slip & Fall Prevention Secrets](#)

[PIG® Grippy® Floor Mats](#)

[29 CFR 1910.22\(a\)\(2\)](#)

Disclaimers

[Safety Instructions Regarding Flammable Liquids for Flame Resistant Mats](#)

Pig Absorbent Mats are flame resistant in their unused state, but take on the properties of flammable liquids they absorb. Always take proper precautions against potential ignition in handling and disposal of these mats if they have absorbed flammable liquids. For further assistance, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com